



Relação do aço						
ELEMENTO	AÇO	N	DIAM (mm)	QUANT	C.UNIT (cm)	C.TOTAL (cm)
VB1	CA60	1	5.0	14	75	1050
	CA50	2	6.3	1	93	93
	CA50	3	8.0	2	226	452
VB2	CA50	4	8.0	2	245	490
	CA60	1	5.0	24	125	3000
	CA50	2	8.0	4	722	2888
VB3	CA50	3	8.0	2	713	1426
	CA50	4	8.0	2	761	1522
	CA60	1	5.0	13	125	1625
VB4	CA50	2	8.0	4	394	1576
	CA50	3	8.0	2	385	770
	CA50	4	8.0	2	433	866
VB5	CA60	1	5.0	23	125	2875
	CA50	2	8.0	4	702	2808
	CA50	3	8.0	2	693	1386
VB6	CA50	4	8.0	2	741	1482
	CA60	1	5.0	26	125	3250
	CA50	2	8.0	4	764	3056
VB7	CA50	3	8.0	2	755	1510
	CA50	4	8.0	2	803	1606
	CA60	1	5.0	56	75	4200
VB8	CA60	2	5.0	3	22	66
	CA60	3	5.0	9	65	585
	CA50	4	8.0	2	835	1670
VB9	CA50	5	8.0	2	850	1700
	CA50	6	10.0	24	81	1944
	CA60	1	5.0	24	75	1800
VB10	CA60	2	5.0	3	65	195
	CA50	3	8.0	4	385	1540
	CA50	4	10.0	6	81	486
VB11	CA60	1	5.0	54	75	4050
	CA60	2	5.0	3	22	66
	CA60	3	5.0	6	65	390
VB12	CA50	4	8.0	2	815	1630
	CA50	5	8.0	2	830	1660
	CA60	6	10.0	18	81	1458
VB13	CA60	1	5.0	54	75	4050
	CA60	2	5.0	3	22	66
	CA60	3	5.0	9	65	585
VB14	CA50	4	8.0	2	815	1630
	CA50	5	8.0	2	830	1660
	CA50	6	10.0	24	81	1944
VB15	CA60	1	5.0	24	75	1800
	CA60	2	5.0	3	65	195
	CA50	3	8.0	4	385	1540
VB16	CA50	4	10.0	6	81	486
	CA60	1	5.0	50	75	3750
	CA60	2	5.0	3	65	195
VB17	CA60	3	5.0	3	59	177
	CA50	4	8.0	2	785	1570
	CA50	5	8.0	2	800	1600
VB18	CA50	6	10.0	12	81	972